

200207269-1

10/664,687

IN THE CLAIMS:

The status and content of each claim follows:

1. (currently amended) An ink delivery apparatus comprising a chamber configured to contain ink, said chamber having:
a proximal end ~~for connection to said ink delivery apparatus;~~ and
opposing side portions having at least one section with a tapered thickness ~~section~~ configured to support said chamber and to facilitate at least partial controlled collapse of said chamber in response to a negative pressure.
2. (original) The apparatus of claim 1, wherein said chamber further comprises a distal end opposite said proximal end, said distal end being rounded.
3. (currently amended) The apparatus of claim 1, further comprising at least one section having a tapered thickness ~~section defined~~ in each of said opposing side portions.
4. (currently amended) The apparatus of claim 3, wherein each opposing side portion comprises a central portion with thickness that decreases ~~of said side portion~~ decreasing to either side of said central portion.
5. (original) The apparatus of claim 1, further comprising rounded side portions at ends of said opposing side portions.
6. (original) The apparatus of claim 1, wherein said chamber comprises an elastomeric material.
7. (original) The apparatus of claim 6, wherein said chamber comprises a EDPM/Butyl material.
8. (original) The apparatus of claim 1, further comprising a fitment coupled to said proximal end of said chamber.

200207269-1

10/664,687

9. (withdrawn) The apparatus of claim 8, wherein said fitment further comprises a fluid interconnect.

10. (withdrawn) The apparatus of claim 9, wherein said fluid interconnect is configured to fluidly couple a print head and said chamber.

11. (withdrawn) The apparatus of claim 10, wherein said chamber comprises an off-axis ink supply.

12. (withdrawn) The apparatus of claim 10, wherein said chamber comprises an on-axis ink supply.

13. (withdrawn) The apparatus of claim 12, wherein said fitment is configured to be coupled to a print head.

14. (withdrawn) The apparatus of claim 1, further comprising a bubble generator in communication with said chamber.

15. (withdrawn) The apparatus of claim 14, wherein said bubble generator is configured to limit said negative pressure within said chamber to a pressure equivalent to about 5 inches of water column during an operational period of said apparatus.

16. (withdrawn) The apparatus of claim 15, wherein said bubble generator disposed in a fitment connected to said proximal end of said chamber.

17. (currently amended) An ink delivery assembly, comprising:
at least one pressure tuned ink chamber having
a proximal end and a distal end; and
a first pair of opposing side walls, each said wall having a thickness and a
section where said thickness tapers ~~portions disposed at least partially between said~~

200207269-1

10/664,687

~~proximal and distal ends, said first pair of opposing side portions having opposing tapered sections; and~~

~~— a second pair of opposing side portions disposed at least partially between said proximal and distal ends, said second pair of opposing side portions having opposing rounded sections; and~~
a fitment coupled to said chamber.

18. (withdrawn) The assembly of claim 17, wherein said fitment further comprises a fluid interconnect.

19. (withdrawn) The assembly of claim 18, wherein said fluid interconnect is configured to fluidly couple a print head and said chamber.

20. (withdrawn) The assembly of claim 19, wherein said fluid interconnect comprises foam and a screen.

21. (withdrawn) The assembly or claim 19, wherein said fluid interconnect comprises a septum

22. (withdrawn) The assembly of claim 19, wherein said fitment further comprises a second fluid interconnect.

23. (withdrawn) The assembly of claim 22, wherein said second fluid interconnect is configured to transmit ink to said chamber and further comprising a plug disposed in said second fluid interconnect.

24. (withdrawn) The assembly of claim 19, wherein said chamber comprises an off-axis ink supply.

25. (withdrawn) The assembly of claim 19, wherein said chamber comprises an on-axis ink supply.

200207269-1

10/664,687

26. (withdrawn) The assembly of claim 19, wherein said fitment is configured to connect directly with a print head.

27. (withdrawn) The assembly of claim 17, further comprising a bubble generator in communication with said chamber.

28. (withdrawn) The assembly of claim 27, wherein said bubble generator is configured to limit said negative pressure within said chamber to a pressure equivalent to about 5 inches of water column during an operational period of said apparatus.

29. (withdrawn) The assembly of claim 28, wherein said bubble generator is disposed in said fitment.

30. (original) The assembly of claim 17, wherein said apparatus further comprises a plurality of pressure tuned ink chambers.

31. (original) The assembly of claim 30, wherein said plurality of pressure tuned ink chambers comprises three chambers.

32. (original) The assembly of claim 30, wherein said plurality of pressure tuned ink chambers comprises a plurality of ink colors, each color being separately contained within one of said plurality of chambers.

33. (original) The assembly of claim 30, further comprising a sealing gasket disposed at least partially between said plurality of chambers and said fitment.

34. (original) The assembly of claim 30, wherein said fitment is configured to be coupled to a print head.

35. (currently amended) A print device, comprising:
at least one pressure tuned ink chamber having
a proximal end and a distal end; and

200207269-1

10/664,687

a first pair of opposing side walls, each said wall having a thickness and a section where said thickness tapers; ~~portions disposed at least partially between said proximal and distal ends, said first pair of opposing side portions having at least one pair of opposing tapered sections,~~

~~— a second pair of opposing side portions disposed at least partially between said proximal and distal ends, said second pair of opposing side portions having opposing rounded sections, and~~

a fitment coupled with said chamber having a fluid interconnect; and
a print head coupled to said fitment.

36. (currently amended) The device of claim 35, further comprising a bubble generator in said fitment, ~~wherein said bubble generator is configured to provide a substantially constant pressure equivalent to about 5" of water column.~~

37. (currently amended) The device of claim 35, wherein said chamber is configured to at least partially collapse in response to a negative pressure to maintain said negative pressure within a determined range, ~~wherein said range is substantially equivalent to pressures of between about 2" and 5" inches of water column.~~

38. (currently amended) The device of claim 35, wherein said ~~opposing tapered sections~~ are opposing and each comprise central portion with thickness of said tapered sections decreasing to either side of said central portion.

39. (original) The device of claim 35, wherein said assembly further comprises a plurality of pressure tuned ink chambers.

40. (original) The device of claim 39, wherein said plurality of pressure tuned ink chambers comprises three pressure tuned ink chambers.